

IEQSA INDUSTRIAS ELECTRO QUIMICAS S.A.

AV. ELMER FAUCETT N° 1920 CALLAO 1 - PERU, P.O. BOX 2130 LIMA
100, PERU, TELEF (51)(1) 572-4444
FAX (51)(1) 572-0118, E-Mail: export@ieqsa.com.pe

TECHNICAL SHEET

ZINC ANODES FOR ELECTROPLATING

Chemical Composition

Lead	: 0.003% max.
Cadmium	: 0.003% max.
Iron	: 0.002% max
Tin	: 0.001% max.
Copper	: 0.001% max
Aluminium	: 0.001% max.
Zinc	: 99.995%

Finish

Clean, bright, without edges

1. Format: ZINC BALLS AND HALF-BALLS

A. Dimensions

50mm and 40mm diameter

B. Packing

Cardboard boxes of approx. 25kg net in wooden pallets of approx. 1 MT, covered and consolidated with stretch film.

Our wooden pallets comply with the norm ISPM N° 15.

2. Format: ZINC HEXAGONS

A. Dimensions

Diameter corner to corner:	19 mm	+/- 0.30 mm
Thickness:	10 mm	+/- 0.30 mm
Average Weight:	16.6 g	+/- 0.50 g

B. Packing

Cardboard boxes of approx. 25kg net in wooden pallets of approx. 1 MT, covered and consolidated with stretch film.

Our wooden pallets comply with the norm ISPM N° 15.

IEQSA INDUSTRIAS ELECTRO QUIMICAS S.A.

AV. ELMER FAUCETT N° 1920 CALLAO 1 - PERU, P.O. BOX 2130 LIMA
100, PERU, TELEF (51)(1) 572-4444
FAX (51)(1) 572-0118, E-Mail: export@ieqsa.com.pe

3. Format: ZINC PLATES

A. Dimensions

According to the specifications of the client. Examples:

10mm thickness, 200mm width, 600mm length

12mm thickness, 250mm width, 600mm length

15mm thickness, 200mm width, 800mm length

16mm thickness, 250mm width, 1400mm length

B. Packing

In wooden pallets of approx. 1 MT, covered and consolidated with stretch film, secured with bands.

Our wooden pallets comply with the norm ISPM N° 15.